

Declaration of performance

No UKSI-15283-003-17 NU Finland

1. Unique identification code of the product-type: Weather Defence/ Type GM-F; GM-H1;

GM-I and **GM-R**

2. Intended use/es: General building works in line with the

standard EN 15283-1+A1: 2009

3. Manufacturer: Etex Building Performance BV

Oosterhorn 32

9936HD Farmsum - the Netherlands

4. Authorised representative: N/A

5. System/s of AVCP: System 3 for Reaction to fire; for all other

performances system 4

6a. Harmonised standard: **NEN 15283-1+A1: 2009**

Notified body/ies: NLE (NB 0071)

6b. European Assesment Document: N/A

European technical assessment: N/A

Technical Assessment Body: N/A

Notified body/ies: N/A

7. Declared performances:

Essential characteristics		Performance		Harmonized technical
				specification
Shear Strength	$\uparrow\downarrow$		NPD	
Reaction to fire	R2F		A1	NEN 15283-1+A1: 2009
				Section 4.2.1
Water vapour permeability	μ		10	
Flexural strength	F	Transverse	≥228 N (9,5mm)	NEN 15283-1 +A1 2009
		direction	≥480 N (20mm)	Section 4.1.1
		Longitudinal	≥725 N (9,5mm)	NEN 15283-1 +A1 2009
		direction	≥1160 N (20mm)	Section 4.1.1
Impact resistance	\rightarrow		System	
			performance	
Direct airborne sound	R		System	
insulation			performance	
Acoustic absorption	α		System	
			performance	
Thermal resistance	λ		0,25W/mK	NEN 520+A1 2009
				Section 4.7





8. Appropriate Technical Documentation and/or Specific Technical Documentation:

www.siniat.nu

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

This DoP replaces SIDE15283001

Signed for and on behalf of the manufacturer by: Neil Ash, Head of Etex BP UK-Irl-Beneno Delfzijl, Netherlands, 8.01.2020

